

OAT Systems / CDSS-Opto22 Compatible Field Devices

<u>Device</u>	<u>Manf</u>	<u>Description</u>	<u>Model</u>	<u>Connection</u>	<u>Opto22 Module</u>
Photoswitch	SICK	Proximity/Diffuse, 10" Range	WT12-2P430	PNP, Digital In	SNAP-IDC5D
Photoswitch	SICK	Proximity/Diffuse, 39" Range	WT12-2P450	PNP, Digital In	SNAP-IDC5D
Photoswitch	SICK	Reflective, 0-18m Range	WL2000-B4300	PNP, Digital In	SNAP-IDC5D
Photoswitch	Omron	Thru-Beam, 7m Range	E3F2-7B4-P1	PNP, Digital In	SNAP-IDC5D
Photoswitch	Micro Detector	Diffuse, 31" Range	FERN-ON-OA	PNP, Digital In	SNAP-IDC5D
Stacklight	Cutler Hammer	R/G/A/B, Horn Option	E26B Series	24VDC, Digital Out	SNAP-ODC5SRC
Stacklight	Allen Bradley	R/G/A/B, Horn Option	855T Series	24VDC, Digital Out	SNAP-ODC5SRC
Motion Sensor	MS Sedco	Microwave	D38	Contact, Digital In	SNAP-IDC5SW
Label Applicator	Diagraph	Bar Coding, Electronic Labeling	PA 5000 LT	24VDC, Digital In	SNAP-IDC5D
Label Applicator	Diagraph	Bar Coding, Electronic Labeling	PA 5000 LT	24VDC, Digital Out	SNAP-ODC5SRC
PLC	Generic	Reed Relay, Normally Open	NA	Contact Relay, Digital Out	SNAP-ODC5R
PLC	Generic	Dry Contact, Normally Open	NA	Contact Relay, Digital In	SNAP-IDC5-SW
Horn	Edwards Signaling	Alarm Horn	870P-N5	120VAC, Digital Out	SNAP-OAC5
Alarm Light	Edwards Signaling	Adaptabeacon LED Alarm Light	104FLEDR-G1	24VDC, Digital Out	SNAP-ODC5SRC